

MAN1216Q43-260

RTK Antenna For GNSS

MECSINE 兆讯

RTK Antenna

For L1/L5 G1 B1/B2a E1/E5a

MAN1216Q43-260

37 x Φ 47.04 mm

All Use For RF & Microwave

Shenzhen Megsine technology co., ltd www.megsine.com sales@megsine.com may contain us for future information
Feb. 03, 2024

MAN1216Q43-260

RTK Antenna For GNSS

MECSINE 兆讯

FEATURES

1. Integrated design of RTK positioning module and helical antenna.
2. Light weight less than 30g.
3. Multi-constellation, multi-frequency support.
4. Wide-voltage input.



DESCRIPTION

The MAN1216Q43-260 is an intelligent positioning antenna that integrates an RTK engine, a helical antenna and a geomagnetic sensor in one compact housing. It provides dual-frequency RTK capability for all constellations, ideal for handheld devices, bike-sharing and two-wheeler rental applications.

MECHANICAL

Characteristic	Specification	Units
Weight	22	g
Dimensions	37 x Φ 47.04	mm
Connector	GH1.25-8P	
Interface Pin Order	1:GND 2:TX2 (NC) 3:RX2 (NC) 4:SDA 5:SCL 6:TX1 7:RX1 8:VCC	

- 2-3 Pin: No Connection; 4~5 Pin: keep open if not used.

ENVIRONMENTAL

Characteristic	Ratings	Units
Operating Temperature Range	-40~+85	°C
Storage Temperature Range	-40~+85	°C
Humidity	95	%

ANTENNA CHARACTERISTICS

Item	Specification	Units
Signal Received	GPS	L1, L5
	GLONASS	G1
	BDS	B1I, B1C, B2a
	Galileo	E1, E5a
	QZSS	L1, L5
Characteristics Impedance	50 (Nominal)	Ω
Polarization	RHCP	
Covering Range	360	°
Peak Gain	2.5	dBi
Out Put VSWR	≤ 2	:1
Axial Ratio (dB)	≤ 3	dB

- Ta: +25 $\pm$ 5°C

All Use For RF & Microwave

MAN1216Q43-260

RTK Antenna For GNSS

MECSINE 兆讯

AMPLIFIER CHARACTERISTICS


Item	Min.	Typ.	Max.
Gain (dB)		23	
Noise Figure (dB)		1.5	2
Output VSWR (:1)			2

- Ta: +25±5°C

SYSTEM SPECIFICATIONS

Item	Specification	Units
Positioning Module	CM260R	
Geomagnetic Sensors	IST8310	
Operation Voltage	5 (3.3-16)	V
Power Consumption	150 (Typical)	mW
Sensitivity (GNSS)	Cold Start: -148; Re-acquisition: -155; Tracking: -164	dBm
RTK Accuracy (RMS)	Horizontal: 10 + 1ppm; Vertical: 30 + 1ppm	cm
Velocity Accuracy (RMS)	0.5	m/s
Time To First Fix	24 (Typical)	s
Initialization Time	< 10 (Typical)	s
Initialize Reliability	> 99.9	%
Data Update Rate	1	Hz

SHAPES AND DIMENSIONS




All Use For RF & Microwave

MAN1216Q43-260

RTK Antenna For GNSS

MECSINE 兆讯



Units: mm

Revision	Description	Date
Rev0	Preliminary	2025/9/18

All Use For RF & Microwave